



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 20

LOCTITE EA 9394 AERO PART A

SDS No. : 234719

V010.1

Revision: 22.04.2025

printing date: 08.05.2025

Replaces version from: 25.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE EA 9394 AERO PART A

UFI: 2VX5-WX4J-T201-5W9V

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Part A of 2-K-Epoxy Adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Germ cell mutagenicity	Category 2
H341 Suspected of causing genetic defects.	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline]

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Signal word:

Warning

Hazard statement:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.
H341 Suspected of causing genetic defects.

**Precautionary statement:
Prevention**

P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing.

**Precautionary statement:
Response**

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration $\geq$ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration $\geq$ the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg. No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
aluminium powder (stabilised) 7429-90-5 231-072-3 01-2119529243-45	25- < 50 %	Water-react. 2, H261 Flam. Sol. 1, H228		EUEXPL2D
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3 249-204-3 01-2119472303-45	25- < 50 %	Muta. 2, H341 Skin Sens. 1, H317 Aquatic Chronic 2, H411		
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3 216-823-5 01-2119456619-26	20- < 40 %	Eye Irrit. 2, H319 Aquatic Chronic 2, H411 Skin Sens. 1, H317 Skin Irrit. 2, H315	Eye Irrit. 2; H319; C >= 5 % Skin Irrit. 2; H315; C >= 5 %	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container.

Store in a cool, dry place.

Ensure that storage and workrooms are adequately ventilated.

Must be stored in a room with spill collection facilities.

Keep away from heat and direct sunlight.

Refer to Technical Data Sheet.

7.3. Specific end use(s)

Part A of 2-K-Epoxy Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Aluminium 7429-90-5 [ALUMINIUM METAL, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Aluminium 7429-90-5 [ALUMINIUM METAL, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Aluminium 7429-90-5 [ALUMINIUM METAL]		1	Time Weighted Average (TWA):		IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Aluminium 7429-90-5	aqua (freshwater)		0,0749 mg/l				
Aluminium 7429-90-5	sewage treatment plant (STP)		20 mg/l				
4,4'-Methylenebis[N,N-bis(2,3- epoxypropyl)aniline] 28768-32-3	aqua (freshwater)		0,005 mg/l				
4,4'-Methylenebis[N,N-bis(2,3- epoxypropyl)aniline] 28768-32-3	aqua (marine water)		0 mg/l				
4,4'-Methylenebis[N,N-bis(2,3- epoxypropyl)aniline] 28768-32-3	aqua (intermittent releases)		0,047 mg/l				
4,4'-Methylenebis[N,N-bis(2,3- epoxypropyl)aniline] 28768-32-3	sewage treatment plant (STP)		1000 mg/l				
4,4'-Methylenebis[N,N-bis(2,3- epoxypropyl)aniline] 28768-32-3	sediment (freshwater)				0,017 mg/kg		
4,4'-Methylenebis[N,N-bis(2,3- epoxypropyl)aniline] 28768-32-3	sediment (marine water)				0,002 mg/kg		
4,4'-Methylenebis[N,N-bis(2,3- epoxypropyl)aniline] 28768-32-3	Air						no hazard identified
4,4'-Methylenebis[N,N-bis(2,3- epoxypropyl)aniline] 28768-32-3	Soil				0,011 mg/kg		
4,4'-Methylenebis[N,N-bis(2,3- epoxypropyl)aniline] 28768-32-3	Predator						no potential for bioaccumulation
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	aqua (freshwater)		0,006 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	Freshwater - intermittent		0,018 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	aqua (marine water)		0,001 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	Marine water - intermittent		0,002 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	sewage treatment plant (STP)		10 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	sediment (freshwater)				0,341 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	sediment (marine water)				0,034 mg/kg		

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Soil				0,065 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	oral				11 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Air						no hazard identified

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Aluminium 7429-90-5	Workers	inhalation	Long term exposure - systemic effects		3,72 mg/m ³	
Aluminium 7429-90-5	Workers	inhalation	Long term exposure - local effects		3,72 mg/m ³	
Aluminium 7429-90-5	General population	oral	Long term exposure - systemic effects		7,9 mg/kg	
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	Workers	inhalation	Long term exposure - systemic effects		3,5 mg/m ³	no hazard identified
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	Workers	dermal	Long term exposure - systemic effects		0,5 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	inhalation	Long term exposure - systemic effects		4,93 mg/m ³	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	dermal	Long term exposure - systemic effects		0,75 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	inhalation	Long term exposure - systemic effects		0,87 mg/m ³	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	dermal	Long term exposure - systemic effects		0,0893 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	inhalation	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	inhalation	Acute/short term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	dermal	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	dermal	Acute/short term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	inhalation	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	inhalation	Acute/short term exposure - local effects			no hazard identified

1675-54-3						
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	dermal	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	dermal	Acute/short term exposure - local effects			no hazard identified

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):nitrile rubber (NBR; ≥ 0.4 mm thickness)Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Delivery form	liquid, paste
Colour	Gray / Grey
Odor	Epoxy
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	< -15 °C (< 5 °F)
Initial boiling point	> 200 °C (> 392 °F)
Flammability	The product is not flammable.

Explosive limits	Not applicable, The product is not flammable.
Flash point	> 93 °C (> 199.4 °F)
Auto-ignition temperature	> 200 °C (> 392 °F)
Decomposition temperature	> 200 °C (> 392 °F);
pH	Product is non-soluble (in water)., Not applicable
Viscosity (kinematic) (40 °C (104 °F);)	> 20 mm ² /s
Viscosity, dynamic (Brookfield; Instrument: HBT; 25 °C (77 °F); Spindle No: 7)	400.000 - 800.000 mPa.s
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Not soluble
Solubility (qualitative) (20 °C (68 °F); Solvent: ketones)	Partially miscible
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure (20 °C (68 °F))	Mixture < 0,1 hPa
Density (20 °C (68 °F))	1,49 g/cm ³ no method / method unknown
Relative vapour density: (20 °C)	> 1
Particle characteristics	Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants.
Reaction with strong acids.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
aluminium powder (stabilised) 7429-90-5	LD50	> 15.900 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	LD50	> 3.000 mg/kg	rabbit	not specified
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
aluminium powder (stabilised) 7429-90-5	LC50	> 5 mg/l	dust/mist	4 h	rat	not specified
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	LC50		vapour	4 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
aluminium powder (stabilised) 7429-90-5	not irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	irritating			Weight of evidence

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
aluminium powder (stabilised) 7429-90-5	not irritating		rabbit	FDA Guideline
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	irritating			Weight of evidence

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
aluminium powder (stabilised) 7429-90-5	not sensitising	Draize Test	guinea pig	Draize Test
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	Sensitizing	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
aluminium powder (stabilised) 7429-90-5	positive	in vitro mammalian cell micronucleus test	without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
aluminium powder (stabilised) 7429-90-5	positive	in vitro mammalian chromosome aberration test	without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
aluminium powder (stabilised) 7429-90-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	positive	mammalian cell gene mutation assay	with and without		other guideline:
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	positive with metabolic activation	bacterial reverse mutation assay (e.g Ames test)	with and without		other guideline:
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
aluminium powder (stabilised) 7429-90-5	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
aluminium powder (stabilised) 7429-90-5	ambiguous	oral: gavage		rat	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	positive	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	positive	oral: gavage		rat	OECD Guideline 489 (In Vivo Mammalian Alkaline Comet Assay)
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	positive	oral: gavage		rat	OECD Guideline 488 (In Vivo Transgenic Cell Gene Mutation Assays)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	negative	oral: gavage		mouse	not specified

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	not carcinogenic	dermal	2 y daily	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	not carcinogenic	oral: gavage	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
aluminium powder (stabilised) 7429-90-5	NOAEL P 1.000 mg/kg NOAEL F1 1.000 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	NOAEL P >= 50 mg/kg NOAEL F1 >= 750 mg/kg NOAEL F2 >= 750 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	NOAEL 50 mg/kg	oral: gavage	14 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains / surface water / ground water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	LC50	7 mg/l	96 h	Cyprinus carpio	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	LC50	1,75 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	EC50	6,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	EC50	1,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	NOEC	0,32 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	EC50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	EC50	> 11 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	NOEC	4,2 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	IC50	> 10.000 mg/l	24 h	Pseudomonas sp.	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	not readily biodegradable.	aerobic	48 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	inherently biodegradable	aerobic	100 %	60 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

No substance data available.
No data available.

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	2,12	22 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	3,242	25 °C	EU Method A.8 (Partition Coefficient)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
aluminium powder (stabilised) 7429-90-5	According to Annex XIII to Regulation (EC) No 1907/2006, a PBT and vPvB assessment shall not be conducted for inorganic substances.
4,4'-Methylenebis[N,N-bis(2,3-epoxypropyl)aniline] 28768-32-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information**14.1. UN number or ID number**

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tetraglycidyl diaminodiphenylmethane,Bisphenol-A Epichlorhydrin resin)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tetraglycidyl diaminodiphenylmethane,Bisphenol-A Epichlorhydrin resin)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tetraglycidyl diaminodiphenylmethane,Bisphenol-A Epichlorhydrin resin)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tetraglycidyl diaminodiphenylmethane,Bisphenol-A Epichlorhydrin resin)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Tetraglycidyl diaminodiphenylmethane,Bisphenol-A Epichlorhydrin resin)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine Pollutant
IATA	Environmentally Hazardous

14.6. Special precautions for user

ADR	not applicable
-----	----------------

	Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG), NZ 4.3(10) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	< 3 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H228 Flammable solid.
H261 In contact with water releases flammable gases.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H341 Suspected of causing genetic defects.
H411 Toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.